



PROPSPEED ETCHING PRIMER HARDENER

Safety Data Sheet

Section 1 - Identification of the Material and the Supplier

1.1 Product identifier

Product name	Propspeed Etching Primer Hardener
Product code	Component in Propspeed kits: PSLKIT, PSMKIT, PSSKIT, PSCKIT, 782A(1 L), RPS500 (500ml), RPS200 (200mL), or Etching Hardener kit (782BC), EPKIT.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Metal Primer Hardener (Part B)
Restrictions of use	Refer to Section 15

1.3 Details of the supplier of the Safety Data Sheet

Supplier	Propspeed USA Inc. 8333 NW 53rd Street Suite 450 Doral, FL 33166 USA www.propspeed.com +1 754 346 4466
-----------------	---

1.4 Emergency telephone number

Emergency Response Telephone (24 hours, 365 days)	USA & Canada - Call CHEMTREC Toll Free: 1-800-424-9300 +1-703-527-3887 New Zealand 0800 243 622 Australian 1800 127 406 Global Access +64 4 917 9888
--	--

NZ National Poisons Centre Telephone	0800 POISON (0800 764 766)
---	----------------------------

Date of SDS Preparation	29 April 2024, Version 2
--------------------------------	--------------------------

PROPSPEED ETCHING PRIMER HARDENER

Safety Data Sheet

Section 2 - Hazards identification

Hazardous Status: This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval Code: Surface Coatings and Colourants (Flammable, Corrosive)- HSR002663

GHS pictograms:



Flammable



Corrosive

GHS Signal word: **Danger**

HSNO Classification	Hazard Code	Hazard Statement	GHS Category
3.1B	H225	Highly flammable liquid and vapour.	Flam. Liq. 2
6.1E (oral)	H303	May be harmful if swallowed.	Acute Tox. 5
8.2C	H314	Causes severe skin burns and eye damage.	Skin Corr. 1C
8.3A	H318	Causes serious eye damage.	Eye Corr. 1

Prevention Code	Prevention Statement
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, sparks, open flames or hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilation and lighting.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe fumes, vapours and spray.
P264	Wash hands thoroughly after handling.
P280	Wear protective clothing in Section 8.

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.

PROPSPEED ETCHING PRIMER HARDENER

Safety Data Sheet

P363	Wash contaminated clothing before reuse.
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P370 + P378	In case of fire: Use AFFF alcohol compatible foam or water spray for extinction.

Storage Code	Storage Statement
P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

Disposal Code	Disposal Statement
P501	Dispose of according to local regulations

Section 3 - Composition/information on hazardous ingredients

Ingredient name	CAS No.	Content Weight%
Propan-2-ol	67-63-0	60-100
Phosphoric Acid	7664-38-2	10-20
Non-hazardous ingredients		To balance

Section 4 - First aid measures

Burns	Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.
If in Eyes	Immediately flush with plenty of water. Remove any contact lenses and open eyes wide apart. Call an ambulance and continue flushing during transportation to hospital. Bring these instructions.
If on Skin	Remove contaminated clothing immediately and wash skin with soap and water. Important to remove the substance from the skin immediately. Continue to rinse for at least 15 minutes and seek medical attention.
If Swallowed	Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician immediately.
If Inhaled	Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if needed.

Most important symptoms and effects, both acute and delayed

Symptoms

Ingestion:	May be harmful if swallowed.
Inhalation:	Not applicable
Skin:	Causes severe skin burns.
Eye:	Causes serious eye damage.

Section 5 – Firefighting measures

Hazard Type	Flammable liquid
Hazards from decomposition products	None in particular
Suitable Extinguishing media	Extinguish with carbon dioxide or dry powder.
Precautions for firefighters and special protective clothing	Selection of respiratory protection for fire- fighting: follow the general fire precautions indicated in the workplace.
HAZCHEM CODE	3WE

Section 6 - Accidental release measures

Avoid any exposure. Do not smoke, use open fire or other sources of ignition. For personal protection, see section 8. Follow precautions for safe handling described in this safety data sheet.

Absorb spillage with non-combustible, absorbent material. Do not use sawdust or other combustible material. Collect spillage in metal/plastic container with tight-fitting lid, with indication of the contents.

Section 7 - Handling and storage

Precautions for safe handling:

- Keep out of reach of children.
- Read label before use.

- Read safety data sheet before use.
- Keep away from heat, sparks, open flames and hot surfaces. No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use only non-sparking tools.
- Use explosion proof electrical equipment, ventilation and lighting
- Take precautionary measures against static discharge.
- Avoid breathing fumes and vapours or sprays.
- Wash hands thoroughly after handling.
- Wear protective clothing

Conditions for safe storage:

- Store in a flameproof, well-ventilated area.
- Electrostatic charges may be generated during transfer of product from its container.
- Ensure that all equipment is electrically earthed.
- Keep container closed and store away from water or moisture.
- Vapours may form explosive mixtures with air.
- Do not store with oxidizing agents.
- Store locked up.

Section 8 - Exposure controls/personal protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance	TWA		STEL	
	ppm	mg.m ³	ppm	mg.m ³
Propan-2-ol	400	980		
Phosphoric Acid		1		

USA OSHA Permissible Exposure Limits (PELs) Table Z-1, April 2024. The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short- Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- minute period in the workingday and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply.

Engineering Controls:

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours. An eye wash bottle must be available at the work site. Mix and prepare in a place with efficient exhaust ventilation.

Personal Protection Equipment



Respiratory	In case of inadequate ventilation, use air-supplied full-mask.
Hands	Wear protective gloves. Nitrile gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable. Other types of gloves can be recommended by the glove supplier.
Eyes	Tight fitting safety goggles or face shield should be used. Avoid wearing contact lenses.
Skin	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.
Hygiene	Wash hands after handling. When using do not eat, drink or smoke. Personal protection may not be worn during meal breaks. Personal protection must be kept separate from other clothes. Do not store tobacco, food or beverage in work rooms or areas where the product is used. Contaminated clothing to be placed in closed container until disposal or decontamination. Warn cleaning personnel of chemical's hazardous properties.

Section 9 – Physical and chemical properties

Appearance	liquid
Colour	Transparent liquid (part 8 of two-pot system)
Odour	solvent
Odour threshold	data not available
pH	not applicable (solvent based product)
Boiling point	81°C
Melting point	data not available
Freezing point	data not available
Flash point	15°C
Flammability	data not available
Upper and lower Explosive Limits	1.1 – 12.0 vol %
Vapour pressure	4266 Pa
Relative vapour density	1.4-1.7(air= 1)
Specific gravity	0.85 -0.95 g.cm ⁻³
Water solubility	soluble in water

PROPSPEED ETCHING PRIMER HARDENER

Safety Data Sheet

Partition coefficient	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
Viscosity	data not available
Particle Characteristics	data not available

Section 10 – Stability and reactivity

Stability of Substance	Stable under normal usage conditions. Curing time: 10 min – 60 min (20°C)
Possibility of hazardous reactions	Data not Available
Conditions to Avoid	Avoid heat, flames and other sources of ignition.
Incompatible Materials	Avoid contact with alkalis. Avoid contact with oxidisers or reducing agents.
Hazardous Decomposition Products	None in particular.

Section 11 – Toxicological information

Acute Effects:

Swallowed	May be harmful if swallowed.
Dermal	Not applicable
Inhalation	Not applicable.
Eye	Causes serious eye damage.
Skin	Causes severe skin burn.

Chronic Effects:

Carcinogenicity	Not applicable.
Reproductive Toxicity	Not applicable.
Germ Cell Mutagenicity	Not applicable.
Aspiration	Not applicable.
STOT/SE	Not applicable.
STOT/RE	Not applicable.

Ingredient Data

Acute Oral Toxicity

Propan-2-ol	LD ₅₀ (mouse)	=3600 mg/kg
-------------	--------------------------	-------------

Section 12 – Ecotoxicological information

This product is not hazardous to the environment.

Environmental Precautions

Persistence and Degradability	No data available
Bioaccumulation:	No data available
Mobility in Soil	No data available
Other adverse effects	No data available

Section 13 – Disposal considerations

Disposal Method:

Spent media that has removed toxic chemicals should be examined for specific hazards. Dispose of according to Local Regulations.

Ensure any container holding waste product or contaminated spill media is labelled “Hazardous Waste – Flammable” and that the label also has the Flammable Pictogram, waste type identifier, and the business name, address, and phone number.

Precautions or methods to avoid: None know.

Section 14 – Transport information

This product is classified as a Dangerous Good for transport in NZ; NZS 5433:2012

	Road and Rail	Marine Transport (IMDG)	Air Transport (IATA)
UN number	3469	3469	3469
UN proper shipping name	PAINT, FLAMMABLE, CORROSIVE	PAINT, FLAMMABLE, CORROSIVE	PAINT, FLAMMABLE, CORROSIVE
Transport hazard class(es)	3	3	3
Sub class	8	8	8
Packing group	 II	 II	 II

PROPSPEED ETCHING PRIMER HARDENER

Safety Data Sheet

Hazchem	3WE	3WE	3WE
Marine Pollutant			
EmS			

Limited Quantities Statement:

If the product's individual container is below 1L/kg, it can be transported as a non-DG as long as the product packaging is still labelled as per DG requirements and the driver is given safety information in accordance with Chapter 3.4 of the UNRTDG.

Section 15 – Regulatory information

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval Code: Surface Coatings and Colourants (Flammable, Corrosive)] - HSR002663
HSNO Classes: 3.1 B, 6.1 E(oral), 8.2C, 8.3A

HSNO Controls

Trigger quantities for this substance:

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	100L(>5L), 250L (<5L), 50L open (3.1B)
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	250L(3.1B)
Emergency Response Plan	1000L(3.1B)
Secondary Containment	1000L(3.1B)
Fire Extinguishers	At least 2 x 4.5kg powder extinguishers required when 250L is present in a workplace.
Restriction of Use	Only use for the intended purpose.

Section 16 – Other information

Glossary

EC50 Median effective concentration.
EEL Environmental Exposure Limit.
EPA Environmental Protection Authority
HSNO Hazardous Substances and New Organisms

PROPSPEED ETCHING PRIMER HARDENER

Safety Data Sheet

HSW	Health and Safety at Work.
LC50	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD50	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
STOT/SE	Specific target organ toxicity – single exposure
STOT/RE	Specific target organ toxicity – repeated exposure
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

Reference:

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices Nov 2017 edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2012
5. HSW (Hazardous Substances) Regulations 2017

Issue Date: 29 April 2024

Review Date: 29 April 2024

Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS. The information herein is given in good faith, but no warranty, express or implied is made. Please contact the New Zealand distributor, if further information is required.